

## AUDIO AND VIDEO

Inputs 1x USB-C

Outputs 1x 19-pin HDMI type A

Video Resolutions (Max) USB-A Display Link: 1920x1080p @60Hz 8bitNative USB-C: 3840x2160 @30hz 8bit 4:4:4

Supported Standards RGB | USB

Maximum Pixel Clock 300 MHz

## COMMUNICATION AND CONTROL

USB USB-C: USB 3.2 Gen 2x1 | Max Bandwidth: 10GbpsUSB-A (Device Port): USB 3.2 Gen 1 | Max Bandwidth: 5Gbps

## POWER

Power Supply 24V DC 5A

Max Power Consumption Max: 10w | Max with USB-C charging: 70w (60w max charging)

## ENVIRONMENTAL

Operating Temperature +32°F ~ +104°F (0°C ~ +45°C) | 10% ~ 90% non-condensing

StorageTemperature -4°F to ~ 140°F (-20°C ~ +70°C) | 10% ~ 90% non-condensing

Maximum BTU TX: 52 BTU/hr | RX: 63.6 BTU/hr

## DIMENSIONS & WEIGHT

Height With | Without Feet 45mm/1.78in | 35mm/1.38in

Width With | Without Feet 263.6mm/10.38in | 230mm/9.06in

Depth With | Without Handles 139mm/5.48in

Weight 1.08kg/2.4lbs

## REGULATORY

Safety and Emission CE | FCC | RoHS | EAC | RCM