

Gefen EXT-UHDA-HBT2 4K Ultra HD HDBaseT 2.0 Extender (Receiver/Sender) Kit with Ethernet/RS-232/IR/POH

- Maximum Pixel Clock: 300 MHz
- Video Input connector (Sender): (1) HDMI Type A 19-pin, female, locking
- Video Output connector (Receiver): (1) HDMI Type A 19-pin, female, locking
- Link connector (Sender/Receiver): (1) RJ-45, shielded, female
- Ethernet port (Sender/Receiver): (1) RJ-45, shielded, female
- RS-232 port (Sender): (1) DB-9, female
- RS-232 port (Receiver): (1) DB-9, male
- Optical Digital Audio Input connector (Receiver): (1) TOSLINK®, female
- Optical Digital Audio Output connector (Sender): (1) TOSLINK®, female
- Analog L/R Stereo Audio Input connector (Sender): (2) RCA, female
- Analog L/R Stereo Audio Output connector (Receiver): (2) RCA, female
- IR Ext/In port (Sender/Receiver): (1) 3.5mm mini-stereo jack
- IR Extender type: EXT-RMT-EXTIRN
- IR Out port (Sender/Receiver): (1) 3.5mm mini-mono jack
- USB port (Sender/Receiver): (1) Mini-B (for Gefen Syner-GTM interface)
- Power/Video/Link Indicator LEDs (Sender/Receiver): (1) Blue, (1) Amber, (1) Green Power Supply connector (Sender/Receiver): (1) 48V DC, locking
- Power Consumption (Sender and Receiver combined): 14W
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +185 °F (-20 to +85 °C)
- Storage Humidity: 0% to 95% RH, non-condensing
- MTBF: 50000 hours
- Dimensions (W x H x D, Sender/Receiver, not including connectors): 8.4" x 1" x 4" (214mm x 25mm x 100mm)
- Net Weight (Sender/Receiver): 0.75 lbs (0.35 kg) each
- Shipping Weight: 4.5 lbs. (2.0 kg)