

Avenview HDM3D-C5HD-R HDMI 3D Extender (Receiver) Single CAT5/6 with HDCP Key Code

ITEM	DESCRIPTION
UNITS	HDM3D-C5HD-R
UNIT DESCRIPTION	HDMI Receiver
HDMI COMPLIANCE	Yes
HDCP	Yes with Key Code
VIDEO BANDWIDTH	Single Link 225 MHz (6.75Gbps)
SUPPORTED RESOLUTIONS	480i / 480p / 720p / 1080i / 1080p60
RESOLUTION AND DISTANCE @ 8-bit	Full HD: (1080p) ~ 40meter (130feet) (CAT5e) / 45meter (140feet) (CAT6) HD: (720p/1080i) ~ 50meter (165feet) (CAT5e)
AUDIO SUPPORT	Surround Sound (up to 7.1 Ch) or Stereo Digital Audio
EQUALIZATION	Min-Max Level Digital Control
INPUT TMDS SIGNAL	1.2 Volts (peak-to-peak)
INPUT DDC SIGNAL	5 Volts (peak-to-peak, TTL)
ESD PROTECTION	- Human body model — ±19kV (air-gap discharge) & ±12kV (contact discharge) - Core chipset — ±8kV
INPUT	1 x RJ45
OUTPUT	1 x HDMI
HDMI CONNECTOR	Type A (19 pin female)
RJ45 CONNECTOR	WE/SS 8P8C with 2 LED indicators
DIMENSIONS (L X W X H)	3" x 3.5" x 1.1"
POWER SUPPLY	5V 2A DC
POWER CONSUMPTION	1 Watt (max)
ENVIRONMENTAL	

OPERATING TEMPERATURE	32° ~ 104°F (0° to 40°C)
STORAGE TEMPERATURE	-4° ~ 140°F (-20° ~ 60°C)
RELATIVE HUMIDITY	20~90% RH (no condensation)