

Avenview SPLIT-HD42K-4 1x4 HDMI 4K UHD Splitter with 1080P 3D ULTRA HD Support

ITEM	DESCRIPTION
UNITS	SPLIT-HD42K-4
UNIT DESCRIPTION	ULTRA HD 4K SPLITTER
HDMI COMPLIANCE	YES
HDCP	Compliant
DATA RATE	10.2Gbps
HDMI SUPPORTED RESOLUTIONS	480i @ 60Hz, 480p @ 60Hz, 576i @ 50Hz, 576p @ 50Hz, 720p @ 50/60Hz/3D, 1080i @ 50/60Hz, 1080p @ 24Hz / 50/60Hz/3D, ULTRA HD (3840x2160)@24Hz 4K x 2K @ 24Hz
PC SUPPORTED RESOLUTIONS	640x480 @ 60Hz, 800x600 @ 60Hz, 1024x768 @ 60Hz, 1280x720 @ 60Hz, 1280x768 @ 60Hz, 1280x960 @ 60Hz, 1280x1024 @ 60Hz, 1360x768 @ 60Hz, 1366x768 @ 60Hz, 1400x1050 @ 60Hz, 1600x900 @ 60Hz, 1680x1050 @ 60Hz, 1920x1080 @ 60Hz (1920x1080@60Hz)
HDMI CABLE	4K2K: (3840X2160@24Hz) ~ 15meter (50feet) FULL HD: (1080p) ~ 15meter (50feet)
AUDIO SUPPORT	LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS-HD Master Audio
INPUT TMDS SIGNAL	1.2 Volts (peak-to-peak)
INPUT DDC SIGNAL	5 Volts (peak-to-peak, TTL)
ESD PROTECTION	Human body model — ±8kV (air-gap discharge) & ±4kV (contact discharge)
INPUT	1 x HDMI Type A (19 pin female)
OUTPUT	4 x HDMI Type A (19 pin female)
LED	Front Panel Indicators
DIMENSIONS (L X W X H)	6.1" x 3.1" x 0.7" 156(L)x79(W)x17(H)mm
WEIGHT	0.5lbs 205g
POWER SUPPLY	5V / 1A DC (US/EU standards, CE/FCC/UL certified)
POWER CONSUMPTION	6 Watt (max)

ENVIRONMENTAL	
OPERATING TEMPERATURE	32° ~ 104°F (0° to 40°C)
STORAGE TEMPERATURE	-4° ~ 140°F (-20° ~ 60°C)
RELATIVE HUMIDITY	20~90% RH (non-condensing)