

Avenview SPLIT-HDM2-T4K-2 1x2 HDMI True 4-60Hz Splitter with AUTO EDID/Management

ITEM	DESCRIPTION	
UNIT	SPLIT-HDM2-T4K-4	SPLIT-HDM2-T4K-8
UNIT DESCRIPTION	ULTRA HD 4K SPLITTER	
HDCP COMPLIANCE	HDCP 2.2	
VIDEO BANDWIDTH	Single-Link 600MHz (18 Hbps)	
HDMI SUPPORTED RESOLUTION	HDR 4K2K@60 (4:2:0 10bits) / 4K2K@60 (4:4:4 8bits)	
SUPPORTED RESOLUTION	480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz/3D, 1080i@50/60Hz,1080p @ 24Hz /50/60Hz/3D, ULTRA HD (3840x2160)@24/30/60Hz 4K (4096x2160)@24/30/60Hz	
HDMI CABLE	15meter (50feet)	
DIGITAL AUDIO SUPPORT	LPCM, Dolby Digital/Plus/EX, Dolby True HD,DTS,DTS-HD Master	
ROTARY CONTROL SWITCH	EDID Mode Selection	
ESD PROTECTION	Human body model — ±8kV (air-gap discharge) & ±4kV (contact discharge)	
INPUT	1 x HDMI Type A (19 pin female)	1 x HDMI Type A (19 pin female)
OUTPUT	4 x HDMI Type A (19 pin female)	8 x HDMI Type A (19 pin female)
DIMENSIONS (L X W X H)	5.46" x 3.67" x 1"	9.5" x 3.9" x 1"
POWER SUPPLY	5V 2A DC	
POWER CONSUMPTION	1.6 W	
LED	Front Panel Indicator	
WEIGHT	0.88 lbs 0.40 kg	3.5 lbs 1.58 kg
ENVIRONMENTAL		
OPERATING TEMPERATURE	32° ~ 104°F (0° to 40°C)	
STORAGE TEMPERATURE	-4° ~ 140°F (-20° ~ 60°C)	
RELATIVE HUMIDITY	20~90% RH (no condensation)	