

Kramer DK22H-N HighSecLabs Dual Head 2-Port 4K30 UHD HDMI KVM Switch

CONSOLE PORTS

- 2 HDMI 1.4 connectors
- 2 USB-A connectors for keyboard and mouse
- 1 3.5mm mini jack for unbalanced stereo audio
- 1 3.5mm mini jack for microphone
- 1 3.5mm mini jack connector for control (RDC)

COMPUTER PORTS

- 4 HDMI 1.4 connectors
- 2 USB-B connectors for keyboard and mouse
- 2 3.5mm mini jacks for unbalanced stereo audio
- 2 3.5mm mini jacks for microphone

MAX RESOLUTION

- Supports resolutions up to 3840×2160

POWER CONSUMPTION

- 12V DC, 1.5A

AC INPUT

- 100 to 240V AC

POWER TYPE

- External

OPERATING TEMPERATURE

- 32° to 104°F (0° to 40°C)

STORAGE TEMPERATURE

- -4° to 140°F (-20° to 60°C)

HUMIDITY

- 0-80% RH, non-condensing

SUPPORTED OS

- Windows, Linux, Mac

PRODUCT CERTIFICATION

- CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

PRODUCT LIFE-CYCLE

- 10 years