

Kramer DK22PH-3 Secure 2-Port 4K DP/HDMI to DP/HDMI Video DH KVM Switch/PP 3.0

SECURE 2 PORT DUAL-HEAD KVM SWITCHES				
Part Number	DK22D-3 DK22D-M	DK22P-3 DK22P-M	DK22H-3 DK22H-M	DK22PD-3 DK22PD-M
No. of Sources	2	2	2	2
Console Ports				
Displays	2 x DVI-I, single-link / dual-link	2 x HDMI 1.4	2 x HDMI 1.4	1 x HDMI 1.4 1 x DVI-I
Mouse & Keyboard	USB Type A	USB Type A	USB Type A	USB Type A
Audio Jack	3.5 mm Jack	3.5 mm Jack	3.5 mm Jack	3.5 mm Jack
fUSB Port	N/A	N/A	N/A	N/A
Computer ports				
Display Type	2 x DVI-I, single-link/dual-link	2 x DisplayPort 1.2	2 x HDMI 1.4	1 x DisplayPort 1.2 1 x DVI-I
Max Resolution	UHD 4K - 3840X2160 @ 30 Hz (via DVI to HDMI cable) DVI dual-link - 2560X1600 @ 60 Hz (via DVI cable)	Supporting UHD 4K resolutions up to 3840x2160 @ 30 Hz	Supporting UHD 4K resolutions up to 3840x2160	Supporting UHD 4K resolutions up to 3840x2160 @ 30 Hz
Mouse and Keyboard	USB Type B	USB Type B	USB Type B	USB Type B
Audio Jack	3.5 mm Jack	3.5 mm Jack	3.5 mm Jack	3.5 mm Jack
fUSB Ports	N/A	N/A	N/A	N/A
Power	Power input 100 to 240V AC External, 12V DC, 1.5A			
Environmental	Operating Temperature: 32° to 104° F (0° to 40° C) Storage Temperature: -4° to 140° F (-20° to 60° C) Humidity: 0-80% RH, non-condensing			
Regulatory Compliance	CE, RCM, FCC class B, VCCI, TUV US, TUV Canada			
Security Accreditations	NIAP Common Criteria PP3.0 for Peripheral Sharing Switch (PSS) devices (DK22x-3 Products Only)			
Physical Characteristics	Dimensions: 177 x 82 x 35 mm / 7 x 3.2 x 1.4 inches Device weight: 0.52 kg (1.1 lbs)			
Warranty, reliability	Product life-cycle 10 years Warranty 2 Years			