Kramer DK42HU-3 HighSecLabs Secure Dual Head 4-Port 4K30 UHD HDMI KVM Switch with fUSB

CONSOLE PORTS

• 2 HDMI 1.4 connectors, 2 USB-A connectors for keyboard and mouse, 1 USB-A connector for USB devices, 2 DIN-5 connectors for PS/2 keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio, 1 RJ45 connector for control (RDC)

COMPUTER PORTS

 8 HDMI 1.4 connectors, 4 USB-B connectors for keyboard and mouse, 4 USB-B connectors for USB devices, 4 3.5mm mini jacks for unbalanced stereo audio

MAX RESOLUTION

• 4K30 UHD (3840X2160 @30Hz)

POWER REQUIREMENTS

• 35W max

AC INPUT

100 to 240V AC

POWER TYPE

Internal

OPERATING TEMPERATURE

• 32° to 104°F (0° to 40°C)

STORAGE TEMPERATURE

• -4° to 140°F (-20° to 60°C)

HUMIDITY

• 0-80% RH, non-condensing

SUPPORTED OS

• Windows, Linux, Mac

SECURITY CERTIFICATION

• NIAP Common Criteria PP3.0 for Peripheral Sharing Switch (PSS) devices

PRODUCT CERTIFICATION

• CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

PRODUCT LIFE-CYCLE

• 10 years