Kramer SK41P-3 HighSecLabs Secure 4-Port/4K30 UHD DisplayPort to HDMI KVM Switch

CONSOLE PORTS

• 1 HDMI connector, 2 USB-A connectors for keyboard and mouse, 2 DIN-5 connectors for PS/2 keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio, 1 RJ45 connector for control (RDC)

COMPUTER PORTS

4 DisplayPort connectors, 4 USB-B connector for keyboard and mouse, 4 3.5mm mini jack for unbalanced stereo audio

MAX RESOLUTION

• 4K30 UHD (3840X2160 @30Hz)

POWER REQUIREMENTS

• 35W max

AC INPUT

• 100V to 240V AC

POWER TYPE

Internal

OPERATING TEMPERATURE

• 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

• -20° to +60°C (-4° to 140°F)

HUMIDITY

• 10% to 80%, RH non-condensing

SUPPORTED OS

• Windows, Linux, Mac

SECURITY CERTIFICATION

• NIAP Common Criteria PP3.0 for Peripheral Sharing Switch (PSS) devices

PRODUCT CERTIFICATION

• CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

WARRANTY

• 3 years

PRODUCT LIFE-CYCLE

• 10 years

PRODUCT DIMENSION

• 34.20cm x 14.90cm x 4.20cm (13.46" x 5.87" x 1.65") W, D, H

PRODUCT WEIGHT

• 1.6kg (3.5lbs) approx.

SHIPPING DIMENSION

• 42.00cm x 24.50cm x 8.50cm (16.54" x 9.65" x 3.35") W, D, H

SHIPPING WEIGHT

• 2.2kg (4.9lbs) approx.