

Panel

Panel Type	VA
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.311 mm
Brightness	300 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)
Viewing Angle (H/V)	178°/178°
Display Colour	16.7M
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze25%),3H Hard Coating

Frequency

Frequency (H)	30 kHz-83 kHz
Frequency (V)	50 Hz-76 Hz

Signal Input

DisplayPort	x 1
HDMI	1.4 x 1
VGA	15-Pin D-Sub x 1

Power

Power Supply	External
Power Requirements	DC 12V 2.5A
On Mode	16W (On)
Standby Mode	< 0.3W
Off Mode	< 0.2W

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	10%-85% (non-condensing)

Storage Conditions

Temperature	-25°C-55°C (-13°F-131°F)
Humidity	5%-93% (non-condensing)

Mounting

Weight

Product with Base	6.1 kg (14.5 lb)
Product w/o Base	3.7 kg (8.2 lb)
Packaging	8.8kg (19.4 lb)

Regulation Approval

Certifications & Compliance	CE LVD WEEE RoHS REACH EAC UKCA BSMI
-----------------------------	---

Accessories

Supplied	HDMI Cable Power Adaptor Power Cord Quick Start Guide Warranty Card
----------	---

Optional Accessories

Ceiling Mount (Landscape only)	CMP-01 + WMK-03
Wall Mount (Landscape only)	PMK-01 WMA-01 WMK-01 WMK-03
Desk mount (Landscape only)	DMC-01 ES-02