

AUDIO:

MUTE	AVAILABLE ON ALL OUTPUTS
ANALOG INPUT VOLTAGE	1VRMS, 2.828 VP-P
ANALOG OUTPUT VOLTAGE	1VRMS, 2.828 VP-P
DIGITAL	2 CHANNEL PCM, SUPPORTED RATES 32, 44.1, 48, 88.2, 96, 176, 192 kHz
LATENCY	30ms

CONTROL:

INTERFACES	RS-232, IP/LAN
------------	----------------

AUDIO INPUTS:

AEX AUDIO	8
RCA	4
DIGITAL (TOSLINK)	4

AUDIO OUTPUTS:

AEX AUDIO	0
RCA	12
DIGITAL (TOSLINK)	12

POWER:

POWER CONSUMPTION (TOTAL)	3 WATTS MAX
DC POWER	DC 12V 1A

DIMENSIONS:

DIMENSIONS (SINGLE UNIT ONLY HEIGHT/WIDTH/DEPTH)	MM: 44.45 x 444.5 x 234.95 INCH: 1.75 x 17.5 x 9.25
DIMENSIONS (PACKAGED HEIGHT/WIDTH/DEPTH)	MM: 127 x 571.5 x 381 INCH: 5 x 22.5 x 15
WEIGHT (SINGLE UNIT ONLY)	6.6 LBS (2.99 KG)
WEIGHT (PACKAGED)	9LBS (4.08KG)

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. MASS & DIMENSIONS ARE APPROXIMATE