

VIDEO:	
VIDEO RESOLUTIONS	UP TO 8K 60Hz 4:2:0/8K 30Hz 4:4:4/4K 120Hz
HDR FORMATS/RESOLUTIONS	420, 422, 444 (10 AND 12 DEEP COLOR) HDR10, HDR10+, DOLBY VISION, HLG
COLOR SPACE	YUV (COMPONENT), RGB (CSC: REC. 601, REC. 709, BT2020, DCI, P3 D6500)
CHROMA SUBSAMPLING	4:4:4, 4:2:2, & 4:2:0 SUPPORTED
DEEP COLOR	UP TO 16 BIT
SCALING (AVAILABLE ON ALL OUTPUTS)	8K TO 4K OR 8K/4K TO 1080P
ADDITIONAL HDMI 2.1 FEATURES	ALLM, VRR, QMS, QFT, HFR
AUDIO:	
AUDIO FORMATS SUPPORTED HDMI	LPCM UP TO 7.1 192 KHZ 24BIT, DOLBY DIGITAL, DOLBY DIGITAL PLUS, DOLBY MAT, DOLBY TRUEHD, DOLBY ATMOS (ALL FORMATS), DOLBY AC-4, DTS DIGITAL, DTS DISCRETE, DTS EXPRESS, DTS HIRES AUDIO, DTS MASTER AUDIO, DTS:X
AUDIO FORMATS SUPPORTED EXTRACTED (TOSLINK)	LPCM UP TO 5.1 96KHZ 24 BIT, DOLBY DIGITAL 5.1, DTS HIRES AUDIO
AUDIO FORMATS SUPPORTED EXTRACTED (2CH PORT)	PCM 2 CH
AUDIO EXTRACTION LOCATION	BIND TO INPUT, BIND TO OUTPUT OR MATRIX (INDEPENDENT)
AUDIO DELAY (PER OUTPUT, EXTRACTED)	UP TO 630ms
DISTANCE: WITH HDMI 2.0 SIGNALS (UP TO 18Gbps - TMDS)	
PASSIVE HDMI IN/OUT	UP TO 10 METERS/32.8 FEET
AOC HDMI IN/OUT	UP TO 100 METERS/328 FEET
DISTANCE: WITH HDMI 2.1 SIGNALS (UP TO 40Gbps - FRL)	
PASSIVE HDMI IN/OUT	UP TO 4 METERS/13.1 FEET
AOC HDMI IN/OUT	UP TO 100 METERS/328 FEET
OTHER:	
BANDWIDTH	40Gbps (FRL 5)
HDCP	1.4, 2.x SUPPORT
CONTROL:	
PORTS	LAN, RS232, IR WINDOW
DRIVERS	C4, RTI, ELAN, CRESTRON, URC (FOR MORE INFORMATION - SEE DRIVERS PAGE ON AVPROEDGE.COM/DRIVERS
AVPro WebUI	YES
PORTS:	
HDMI	TYPE A
LAN	RJ45 W/ WEB INTERFACE/ CONTROL
AUDIO (EXTRACTED DIGITAL)	TOSLINK
AUDIO (EXTRACTED ANALOG)	L/R AUDIO
IR RX	WINDOW ONLY (REMOTE INCLUDED)
RS232	3 PIN TERMINAL BLOCK
ENVIRONMENTAL:	
OPERATING TEMPERATURE	23 TO 125°F (-5 TO 51°C)
STORAGE TEMPERATURE	-4 TO 140°F (-20 TO 60°C)
HUMIDITY RANGE	5-90% RH (NO CONDENSATION)
POWER:	
POWER CONSUMPTION (TOTAL)	129.6 WATTS MAX
POWER SUPPLY - MATRIX	INPUT: AC 100-240V ~ 50/60HZ OUTPUT: DC 48V 2.7A
DIMENSIONS:	
DIMENSIONS (UNIT ONLY - HEIGHT/DEPTH/WIDTH)	MM: 44 X 260.35 X 441.45 INCH: 1.73 X 10.25 X 17.38
DIMENSIONS (PACKAGED HEIGHT/DEPTH/WIDTH)	MM: 88.9 X 444.5 X 495.3 INCH: 3.5 X 17.5 X 19.5
WEIGHT (UNIT)	9 LBS (4 KG)
WEIGHT (PACKAGED)	13 LBS (5.6 KG)
*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. MASS & DIMENSIONS ARE APPROXIMATE	