

SPECIFICATIONS

Technical

- AV Inputs: 1x HDMI, 1x USB C
- AV Outputs: 1x CAT6/6A RJ45
- DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL)
- HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p
- USB C Signal: Input Video Signal: 1.2 Volts p-p
- RJ45 Connectors: Shielded Link Connector, CAT6/6A
- RS-232 Connector: 3-pin phoenix terminal
- IR: 1x IR Sensor at Tx unit, 1x 3.5mm mono output at Rx unit

General

- Regulation: CE, RoHS, WEEE, EAC
- Wall plate: U.S. 1-gang wall plate in aluminum enclosure
- Decora plate: Brushed aluminum
- Product Dimensions (Tx): 1.92 x 4.13 x 1.42" (49 x 105 x 36.2 mm)
- Product Weight: Weight (Tx): 0.6 lbs (0.27 kg)
- Product Dimensions (Rx): 4.3" x 4.12" x 0.82" (109.2 x 104.6 x 20.8mm)
- Product Weight: Weight (Rx): 0.595 lbs (0.27 KG)
- Packaging Dimensions: 10.23 x 5.67 x 3.15" (260 x 144 x 80mm)
- Packaging Weight: 1.98lbs 0.9 kg