

Shinybow SB-5669K 16x16 UHD 4K2K HDMI Matrix Routing Switcher w/ Full EDID

- Signals Supported: HD 1080p-60Hz, H36-bit Deep color, 3D (1.4a) formats
- HDCP / CEC: HDCP V1.3 Compliant, 4K2K/60Hz HDCP V2.2, CEC Compliant
- Video Bandwidth: Double Data Rates: 225Mhz, Total 10.2Gbps bandwidth
- Digital Video Supported:
 - Full HD resolution: 480i/480p/720p/1080i/1080p
 - Digital Audio Supported:
 - Multi Audio Formats 5.1/7.1, MAT (MLP)
 - Dolby Digital
 - Dolby TrueHD
 - Dolby Digital Plus
 - DTS, DTS-ES 6.1
 - DTS-HD, DTS-HD-HRA, DTS-HD Master
 - (PCM-2CH)
- Controls:
 - IR Wireless Remote Controller, Ethernet
 - IR External port 1x (OD 3.5mm Ear phone Jack)
 - Front panel buttons
 - RS-232
- IR Extender Distance: 1,000 ft
- Infrared Frequency: 38KHz
- Safety Approvals: CE, FCC, RoHS (2002/95/EC)
- Switcher Size (WxDxH): 19* x 9.85 x 1.75 in (*with rackmount bracket) (482 x 250 x 44 mm)
- RS-232 Cable: Straight thru, 6 ft, 9D-M to 9D-F
- Environment: Operational; 32 F - 100 F (0 C - 38 C)
- Power Source: Input: 100-240VAC, 50-60Hz 1.2A