

A-NeuVideo ANI-PIP-41UHD 4x1 4K60 UHD Quad/PiP/PoP Multiviewer Seamless Video Switcher

- **Input Ports:** (4) HDMI IN [Type A, 19-pin female]
- **Output Ports:**
 - HDMI OUT [Type A, 19-pin female]
 - L/R OUTPUT [RCA]
 - OPTICAL OUTPUT [S/PDIF]
- **Control Ports:**
 - RS-232 [3pin-3.81mm phoenix connector]
 - IR EXT [3.5mm Stereo Mini-jack]
- **HDMI Compliance:** HDMI 2.0b
- **HDCP Compliance:** HDCP 2.2 / 1.x
- **Video Bandwidth:** 18Gbps
- **Video Resolution:** Up to 4K@60Hz
- **IR Level:** 5Vp-p
- **IR Frequency:** 38KHz
- **Color Space:** RGB, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0
- **Color Depth:** 8bit
- **Audio Formats:**
 - **HDMI:** PCM2.0/5.1/7.1CH, Dolby Digital/Plus, DTS, DTS High Res
 - **Analog audio [3.5mm L/R]:** PCM2.0
 - **SPDIF (OPTICAL):** Dolby Digital, DTS 5.1, PCM2.0
 - Note: It does not support HBR audio. For example Atmos.
- **ESD Protection:** Human Body Model:
 - ±8kV (air-gap discharge)
 - ±4kV (contact discharge)
- **Housing:** Metal Enclosure
- **Color:** Black
- **Dimensions (WxDxH):** 8.7 x .22 x 1.2 in (220x100x30mm)
- **Weight:** 1.4 lb / 620g
- **Operating Temperature:** 0°C~40°C/ 32°F~104°F
- **Storage Temperature:** -20°C ~ 60°C/-4°F ~140°F
- **Relative Humidity:** 20~90% RH (non-condensing)
- **Power Consumption (Max):** 10W (Max)
- **Power Supply:** Input: AC 100 - 240V 50/60Hz / Output: DC 12V/2.5A (US/EU standard, CE/FCC/UL certified)