

A-NeuVideo ANI-PIP-42UHD 4x2 4K60 UHD Multiviewer Seamless Video Matrix Switcher

- **Input Ports:** (4) HDMI IN [Type A, 19-pin female]
- **Output Ports:**
 - (2) HDMI OUT [Type A, 19-pin female]
 - (2) L/R OUTPUT [RCA]
 - (2) OPTICAL OUTPUT [S/PDIF]
- **Control Ports:**
 - RS-232 [3pin-3.81mm phoenix connector]
 - IR EXT [3.5mm Stereo Mini-jack]
- **HDMI Compliance:** HDMI 2.0b
- **HDCP Compliance:** HDCP 2.2 / 1.x
- **Video Bandwidth:** 18Gbps
- **Video Resolution:** Up to 4K2K@60 4:4:4
- **IR Level:** 5Vp-p
- **IR Frequency:** 38KHz
- **Color Space:** RGB, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0
- **Color Depth:** 8/10/12-bit
- **Audio Formats:**
 - HDMI Audio: PCM2.0/5.1/7.1CH, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio
 - Analog audio [3.5mm L/R]: PCM2.0
 - Optical fiber audio: PCM2.0/5.1/7.1CH, Dolby Digital/plus, DTS 5.1
- **ESD Protection:** Human Body Model:
 - ±12kV (Air Discharge)
 - ±8kV (Contact Discharge)
- **Housing:** Metal Enclosure
- **Color:** Black
- **Dimensions (WxDxH):** 10.6 x 5.1 x 1.2 in (270x130x30mm)
- **Weight:** 2 lb / 906g
- **Operating Temperature:** 0°C~40°C/ 32°F~104°F
- **Storage Temperature:** -20°C ~ 60°C/-4°F ~140°F
- **Relative Humidity:** 20~90% RH (non-condensing)
- **Power Consumption (Max):** 15.72W (Max)
- **Power Supply:** Input: AC 100 - 240V 50/60Hz / Output: DC 12V/2.5A (US/EU standard, CE/FCC/UL certified)
 - ANI-PIP42UHD 4K60 4x2 Multiviewer Seamless UHD Video Matrix Switcher
 - IR Remote
 - 3pin-3.81mm Phoenix Connector (male)
 - 38KHz IR Wideband Receiver Cable (1.5 meters)
 - (2) Mounting Ears
 - (4) Machine Screws (KM3*4)
 - 12V/2.5A Locking Power Adapter
 - Users Guide