



use solution to connect devices to HSL's KVMs.



USB Type-C to DP Dual-Head KVM Cable System Diagram



USB Type-C to DP SH KVM Cable System Diagram



## SPECIFICATION

MODEL NUMBER	SCBLN11CL	SCBLN11CCL	DCBLN12CCL
FEATURES			
Input Interface (Host)	LAN + Type-C	LAN + Type-C	LAN + Type-C
Output Interface (Video)	_	4K 60HZ Single Head	4K 30HZ Dual Head, 4K 60HZ Single Head
USB Compliance	_	USB 2.0	USB 2.0
Charging	PD 2.0 complaint up to 100W	PD 2.0 complaint up to 100W	PD 2.0 complaint up to 100W
Cable length	3ft USB C	3ft USB C, 1 x 6FT Video and USB	3ft USB C, 2 x 6FT Video and USB
Network	100MB	100MB	100MB
PHYSICAL			
Dimensions	129.5 x 65.4 x 17 mm / 5.1 x 2.6 x 0.7 inch	142.5 x 65.4 x 17 mm / 5.6 x 2.6 x 0.7 inch	
Weight			
ENVIRONMENTAL			
Operating Temperature	- 0°C to 40°C (32°F to 104°F)		
Storage Temperature	-20°C to 60°C (-4°F to 140°F)		
Humidity	Operating - 20 to 80% non-condensing; Storage - 10 to 90% non-condensing		
Altitude	0 to 10,000 ft		
GENERAL INFO			
Made In	ISRAEL/USA		
Product Life-cycle	10 years		
Warranty	2 Years		

