

## Input / Output

Transmitter	3G/HD-SDI input×1, loop output ×1
	HDMI 1.3 input×1
Receiver	3G/HD-SDI output×2
	HDMI 1.3 output ×1

## Video Formats

SDI	1080p60, 1080p59.94, 1080p50
	1080p23.98, 1080p24; 1080p25, 1080p29.97, 1080p30;
	1080psf23.98, 1080psf24
	1080i60, 1080i59.94, 1080i50;
	720p60, 720p59.94, 720p50
HDMI	1080p60, 1080p59.94, 1080p50
	1080p23.98, 1080p24; 1080p25, 1080p29.97, 1080p30;
	1080psf23.98, 1080psf24
	1080i60, 1080i59.94, 1080i50;
	720p60, 720p59.94, 720p50

## Wireless

Frequency	5.17GHz-5.23GHz and 5.75GHz-5.83GHz
RF Modules	OFDM 16QAM, 64QAM, QPSK, BPSK
RF Power	125mW
Transmission Distance	2000 feet / 600 meters (Line of sight)

## General

Input voltage	Transmitter DC 7-34V Reveiver DC 7-34V
Power Consumption	Transmitter 8W Reveiver 8W
Dimension(w/o antenna)	Transmitter 66×106.5×24.7 (mm) Reveiver 106.5×66×24.7 (mm)
Net weight	Transmitter 236g Reveiver 245g
Working Temperature	0°C -+40°C

