

SWIT S-1173F 17.3-inch Full HD Waveform Studio 2K/3G/HD-SDI/HDMI/YUV/VGA/CVBS LCD Monitor

LCD Performance		
Size	17.3 inches	
Display area	381.89×214.8mm	
Resolution	1920×1080	
Aspect ratio	16:9 (4:3 adjustable)	
Brightness	300cd/m2	
Contrast	700:1	
Color	16.77 million colors	
Viewing	Horizontal: 160°Vertical: 160°	
Input		
BNC ×2	2K/3G/HD/SD-SDI inputx2	
BNC ×1	CVBS input	
BNC ×3	Y/Pb/Pr input	
HDMI ×1	HDMI input	
RS485 ×2	GPI×1, UMD×1	
RS232C ×1	UMD	
VGA ×1	VGA input	
3.5mm RCA ×2	L/R audio input	
USB ×1	USB input (firmware upgrade)	
Output		
BNC ×2	2K/3G/HD/SD-SDI loop output	
BNC ×1	CVBS Loop output	
HDMI ×1	HDMI loop output	
RS485 ×1	UMD×1	
3.5mm ×1	SDI/HDMI embedded audio output, analog audio output	
Video Format		
CVBS	NTSC/PAL	
SDI	SMPTE ST 2048-1: 2011	2048×1080p (60/59.94/50/30/29.97/25/24/23.98)
	SMPTE-425M	1080p (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/23.98)
	SMPTE-RP211	1080psf (30/29.97/25/24/23.98)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
HDMI	480i/ 576i / 480p / 576p	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
Y/Pb/Pr	480i/576i/480p/576p,720p(50/60),1080i(50/60),1080p(50/60)	
VGA	640×480/800×600/1024×768/1152×864/1280×768	
	1280×960/1280×1024/1600×1200	
General		
Working voltage	AC: 100V-240V DC: 11V-17V	
Power consumption	≤32W	
Working temperature	0°C+40°C	
Working humidity	10%90%	
Storage temperature	-15°C+60°C	
Storage humidity	10%90%	
Dimensions	430×310×73mm	

Net weight (w/o stand)

4.65kg (or 10.3 lbs)