

# ConferenceSHOT FX

USB 3.0 Fixed Camera

## ORDERING INFORMATION

### Black:

999-20000-000 (North America)

999-20000-001 (Europe/UK)

### White:


999-20000-000W (North America)

999-20000-001W (Europe/UK)



## OVERVIEW

The ConferenceSHOT™ FX is a fixed USB camera with network manageability, providing professional quality at an entry level price. The ConferenceSHOT FX is capable of 1080p/60fps for the smoothest video available through the USB 3.0 output. Frame the whole group better with an extra-wide 88° horizontal field of view. For small conference rooms and huddle spaces that need a simple camera setup, the ConferenceSHOT FX is the perfect solution – an enterprise-class USB camera that plugs into a USB port and simply works with major UCC soft clients.



## CONNECTOR PANEL

- **12 VDC, 1.5 amp power connector** – Connect only the power supply shipped with the camera
- **USB 3.0 type B video device connector** – Streams uncompressed UVC standard video
- **Ethernet RJ-45** – Connect to the network for IP streaming and camera control via web interface or Telnet
- **RS-232 port** – Connect to a controller to manage the camera using a modified VISCA protocol
- **DIP switches** – Set IR frequency and image flip (camera is invertible)

## WHAT'S INCLUDED

- ConferenceSHOT FX Camera
- Thin Profile Wall Mount with mounting hardware
- 12 VDC, 1.5 Amp switching power supply with AC plug adapters
- USB 3.0 Type A to Type B cable, 6 ft. (1.8 m)
- Remote control
- Quick Start Guide

## FEATURES

- 2 Megapixels, full HD image sensor (native 1080p/60)
- 3x optical zoom with 88° horizontal field of view
- Simultaneous uncompressed USB 3.0 and IP (H.264) streaming outputs at resolutions up to 1080p/60
- Selectable IP stream resolution; USB stream resolution auto-negotiated with conferencing client
- Universal Video Class (UVC) drivers supported in Windows®, Mac® OS, and Linux operating systems, compatible with most UC conferencing applications
- Presenter-friendly IR remote control
- Integration-ready Telnet or serial RS-232 control
- Full administrative control via web interface; manage remotely while monitoring the stream separately.

## TECHNICAL SPECIFICATIONS

Camera & Image	<b>Image device</b>	1/2.8-type Exmor® CMOS sensor, full HD
	<b>Pixels</b>	2.14 million (effective), 2.38 million (total)
	<b>Lens</b>	3x optical zoom, f=4.7mm wide end to 94mm tele end, F1.6 to F3.5
	<b>Horizontal FOV</b>	88° wide end to 46° tele end
	<b>Min. working distance</b>	10mm (wide), 1m (tele)
	<b>Max. installation height</b>	30 ft (9.1 m)
	<b>Min. illumination</b>	100+ lux recommended
	<b>Backlight compensation</b>	On/off
	<b>Aperture/detail</b>	16 steps
	<b>Focusing system</b>	Auto / Manual
	<b>Gain</b>	Auto / Manual
	<b>White balance</b>	Auto / Manual
	<b>S/N ratio</b>	More than 50 dB
	<b>Sync system</b>	Internal
	<b>Power</b>	12 VDC, 1.5 A
<b>Remote management</b>	IR Remote, web interface, Telnet and RS-232 command APIs	
Physical & Environmental	<b>Weight</b>	2.5 lbs (1.1 kg)
	<b>Height</b>	6.3" (163 mm)
	<b>Width</b>	6.1" (155 mm)
	<b>Depth</b>	5.5" (145 mm)
	<b>Operating/storage temperature</b>	0°C to +40°C (32°F to 104°F)
	<b>Operating/storage humidity</b>	20% to 80% RH, non-condensing

Specifications are subject to change without notice.

## BASIC CONNECTION

Here is an example of how the camera might be set up in a conference room. In this setup, a computer uses a unified communications conferencing application with the camera and a conference phone.



# vaddio®

THE ART OF EASY | legrandav.com

USA P 800.572.2011 E av.vaddio.support@legrand.com  
 EMEA P +31.495.580.840 E av.emea.sales@legrand.com  
 APAC P +852.2145.4099 E av.asia.sales@legrand.com

legrand® | AV

©2020 Legrand AV Inc. 180030 rev. C 06/2020 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending

COMMERCIAL BRANDS  
 C2G | Chief | Da-Lite | Middle Atlantic | Projecta | Vaddio