

Color	Black
Certifications	CE Approved, FCC Approved
Product Width	6.1" (15.49 cm)
Product Height	6.3" (16.00 cm)
Product Depth	5.5" (13.97 cm)
Product Weight	2.5 lbs (1.13 kg)
Signal Type	USB 3.0, IP-Streaming
Power Type	Local Power
Output Ports	USB 3 Type B, IP-Streaming
Zoom	3x optical zoom
Field of View	88° Wide End to 46° Tele End
Estimated Room Size	Huddle Space, Small Conference Room
Minimum Illumination	0.15 Lux (F1.5)
Browser-based User Interface for Remote Control	Built-in
Control Method	Web UI, Telnet, RS-232 and IR Remote
OneLINK Compatibility	No
PTZ Motors	No Motors-Manual
Tri-Sync Motion	No
Pan and Tilt Range	Fixed: Pan (Manual): ±170°, Tilt (Manual): +90° to -30°
Image Sensor Type	1/2.8 Exmor CMOS
Pixels	2.14 Megapixel (2.38 Total MP)
Top Resolution	1080p/60
Invertible	Yes
Video S/N Ratio	greater than 50 dB
Gain	Auto, Manual
Operating Temperature	32° to 104°F (0° to 40°C)
Warranty	2 years
Power Supply	12 VDC, 1.5 A
Quick-Connect Compatibility	No