## 

Compatible Cameras:	Vaddio, Panasonic, Sony & Canon (See Manual for Specific Models)
Video Formats Supported:	NTSC and PAL
Video Switcher:	6 x 2 (or Two 6x1 in Dual Mode)
Video Transitions:	Cross Fade, 9 Wipe options and Straight Cuts, Fade to Black
Video Inputs:	Five (5) DE-15-F: RGBHV, HD Component (YPbPr), or Y/C & Composite using adapter cables One (1) DVI-I (both DVI-D and DVI-A): HDMI 1.3 Receiver, Compliant with DVI 1.0 and HDMI 1.3
Preview or Multiviewer Output:	One (1) DE-15-F Preview or Multiviewer Output: RGBHV, HD Component (YPbPr), or Y/C & Composite using adapter cables One (1) DVI-D Preview or Multiviewer Output: HDMI 1.3 Transmitters, Compliant with DVI 1.0 and HDMI 1.3 Note: Same resolution on both Preview outputs
Program Output:	One (1) DE-15-F Program Output: RGBHV, HD Component (YPbPr), or Y/C & Composite using adapter cables One (1) DVI-D) Program Output: HDMI 1.3 Transmitters, Compliant with DVI 1.0 and HDMI 1.3 Note: Same resolution on both Program outputs
Camera Control Ports:	Six (6) RS-232 on RJ-45F
Control Interface:	One (1) RS-232 on DB-9
LCD Display:	8-line backlit LCD display
Power Requirements:	PowerRite 18 VDC, 2.78 Amp
Control Inputs for Auto Mode (input 1 & 2):	Cameras 1 & 2 have 6 presets each or Camera 1 can have 12
Tally Output:	Tally outputs for each of the six video inputs
Weight:	9.5 lbs. (4.32kg) - approximate weight
Dimensions (H x W x D):	4" (10.16cm) x 16" (40.64cm) x 10" (25.4cm)