

Blackmagic Design BMD-ULTMKEY12/A/HDM Ultimatte 12 HD Mini

Standards

SD Video Standards

- 525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60 1080i50, 1080i59.94, 1080i60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 424M, SMPTE 425M level A and B.

Video Sampling

- 4:2:2

Color Precision

- 10-bit

Color Space

- REC 601, REC 709.

Multiple Rate Support

- Auto detection of SD and HD.

Composite Sources

Foreground

- 1 x HDMI In

Background

- 1 x HDMI In
- Still from Media Pool

Background Matte

- Internal Window
- Still from Media Pool

Garbage Matte

- Internal Window
- Still from Media Pool

Holdout Matte

- Internal Window
- Still from Media Pool

Layer

Still from Media Pool

Layer Matte

- Internal Window
- Still from Media Pool

Composite Outputs

Program

- 1 x HDMI
- 1 x 3G-SDI

Monitor

Monitor In

- 1 x 3G-SDI for monitor cascade

Monitor Out

1 x 3G-SDI

For monitoring Program, Foreground Input, Background Input, Combined Matte, Internal Matte, Fill Out, Layer Input, Background Matte Input, Garbage Matte Input, Holdout Matte Input, Layer Matte Input, Processed Layer Matte, Processed Holdout Matte, Processed Garbage Matte, Processed Background Matte, Screen Correction.

Media Pool

Background Still Image Formats

- TGA, TIFF, BMP, PNG, JPG.

Background with Alpha Still Image Formats

- TGA, TIFF, BMP.

Layer Image Still Image Formats

- TGA, TIFF, BMP, PNG, JPG.

Layer with Alpha Still Image Formats

- TGA, TIFF, BMP.

Garbage Matte Still Image Formats

- TIFF, BMP, PNG, JPG.

Holdout Matte Still Image Formats

- TIFF, BMP, PNG, JPG.

Media Pool Memory

- 6GB non-volatile internal storage.

Displays

Built in 2.2 inch color display for device name, video preview, video standard audio meters, status and menus.

Control

Front Panel

2.2 inch color display, 3 preset buttons, 3 menu buttons and spin knob.

Control Connection

Network or direct Ethernet connection to a computer running Ultimatte Software Control or Ultimatte Smart Remote 4.

Software Control

Ultimatte Software Control supported on Mac™ or Windows™ computers.

Hardware Control Panel

- Ultimatte Smart Remote 4

Camera Control

Blackmagic camera control and tally supported when used with compatible cameras and ATEM switchers.

Custom Control

Ethernet protocol included in the Ultimatte instruction manual.

Software

Software Updates

Using USB-C or Ethernet connection to Mac™ or Windows™ computers.

Configuration

Ultimatte IP address is set via the front panel or Ultimatte setup utility connected via USB.

Operating Systems

- Mac 11.0 Big Sur,
- Mac 12.0 Monterey or later.
- Windows 10, 64-bit.
- Windows 11.

Power Requirements

Power Supply

- 1 x Internal 100-240V AC, 50/60Hz

Power Usage

- 12W

Accessories

Optional Accessories

- Ultimatte Smart Remote 4

Physical Installation

- One third rack unit width, 1 rack unit height.

Environmental Specifications

Operating Temperature

- 0° to 40°C (32° to 104°F)

Storage Temperature

- -20° to 60°C (-4° to 140°F)

Relative Humidity

- 0% to 90% non-condensing.