

PreSonus Eris E3.5 2-Way 3.5 inch Near Field Studio Monitor (PAIR)

PreSonus® Eris-series studio monitors are used worldwide by audio engineers who need to hear every detail of their recordings. Ideal for gaming and home video production, the Eris E3.5 employs the same technology as the larger Eris models to deliver studio-quality sound, with a smooth and accurate frequency response. Yet they're compact enough to fit almost anywhere.

Inputs	
1- Stereo 1/8"	
2- Balanced ¼" TRS	
2- Unbalanced RCA	
Performance	
Frequency Response	80 Hz - 20 kHz
Crossover Frequency	2.8 kHz
Amplifier Power	25W/speaker
LF Driver	3.5" made with Kevlar®
HF Driver	1" silk dome
Peak SPL (@ 1 meter)	100 dB
Input Impedance	10 kΩ
User Controls	
Volume Range	A-type taper
MF Control	Variable (-6 to +6 dB, center 100 Hz)
HF Control	Variable (-6 to +6 dB, center 10 kHz)
Protection	
RF interference	
Output-current limiting	
Over-temperature	
Turn-on/off transient	
Subsonic filter	
External mains fuse	
Power	
100-120V ~50/60 Hz or 220-240V ~50/60 Hz	
Cabinet	
Vinyl-laminated, medium-density fiberboard	
Physical	
Width	5.6" (141 mm)
Depth	6.4" (162 mm)
Height	8.3" (210 mm)
Weight (per pair)	6.4 lb. (2.9 kg)