

PreSonus Eris E4.5 2-Way 4.5 inch Near Field Studio Monitor (PAIR)

Inputs	
1- Stereo 1/8"	
2- Balanced ¼" TRS	
2- Unbalanced RCA	
Performance	
Frequency Response	70 Hz - 20 kHz
Crossover Frequency	2.8 kHz
Amplifier Power	25W/speaker
LF Driver	4.5" made with Kevlar®
HF Driver	1" silk dome
Peak SPL (@ 1 meter)	100 dB
Input Impedance	10 kΩ
User Controls	
Volume Range	A-type taper
MF Control	Variable (-6 to +6 dB)
HF Control	Variable (-6 to +6 dB)
Low Cut	Flat, 80 Hz, 100 Hz
Acoustic Space	Flat, -2 dB, -4 dB
Protection	
RF interference	
Output-current limiting	
Over-temperature	
Turn-on/off transient	
Subsonic filter	
External mains fuse	
Power	
100-120V ~50/60 Hz or 220-240V ~50/60 Hz	
Cabinet	
Vinyl-laminated, medium-density fiberboard	
Physical	
Width	6.42" (163 mm)
Depth	7.09" (180 mm)
Height	9.45" (241 mm)
Weight (per pair)	13 lb. (5.9 kg)