

PreSonus Eris E66 MTM Dual 6 inch Powered Studio Monitor

Inputs	
1- Balanced XLR	
1- Balanced ¼" TRS	
1- Unbalanced RCA	
Performance	
Frequency Response	45 Hz - 22 kHz
Crossover Frequency	2.4 kHz
LF Amplifier Power	80W
HF Amplifier Power	65W
Peak SPL (@ 1 meter)	106 dB
LF Driver	Dual 6.5" made with Kevlar®
HF Driver	1.25" silk dome
Input Impedance	10 kΩ
User Controls	
Volume Range	A-type taper
MF Control	-6, 0, +6 dB
HF Control	-6, 0, +6 dB
Low Cut	Flat, 80 Hz, 100 Hz
Acoustic Space	Flat, -2 dB, -4 dB
Protection	
RF interference	
Output-current limiting	
Over-temperature	
Turn-on/off transient	
Subsonic filter	
External mains fuse	
Power	
100-120V ~50/60 Hz or 220-240V ~50/60 Hz	
Cabinet	
Vinyl-laminated, medium-density fiberboard	
Physical	
Width	18.1" (460 mm)
Depth	8.5" (215 mm)
Height	9.8" (250 mm)
Weight	23.4 lbs (10.6 kg)