

Aurora Multimedia DXP-62K-3 Presentation Switcher w HDBaseT Extender/Amplifier

| Video | |
|------------------------|---|
| Max HDBT Distance | 230ft (70m) |
| Max Resolution | 1920x1200 @60Hz |
| Color Depth | 36bit |
| Bandwidth | HDMI: 1.65Gbps per color C-Video:150MHz YPbPr: 170MHz VGA: 375MHz |
| Audio | |
| Audio Bandwidth | 20Hz - 20KHz |
| Connectors | |
| RS-232 | Max 115kbps |
| HDMI Inputs | 4 |
| VGA/YPbPr/Video Inputs | 2 |
| HDMI Outputs | 1 |
| HDBaseT Outputs | 1 PoH (Video, RS-232, IR) |
| Audio Inputs | 4 Stereo 3 pin 3.81mm Euro / 1 Mic 3 pin 3.81mm Euro |
| Audio Outputs | 1 Stereo 3 pin 3.81mm Euro / 0db Gain. |
| RS-232 Ports | 1 |
| IR Input Ports | 1 |
| IR Output Ports | 1 |
| IR Frequency Range | 20KHz - 60KHz |
| HDBaseT Connector | RJ-45 WE/SS 8P8C |
| RS-232 Connector | Euro Style 3.81mm |
| IR Connector | 3.5mm TRS |
| HDMI Connector | Type A 19 pin |
| Power Connector | IEC Male |
| Mechanical | |
| Housing | Black Aluminum Enclosure |
| Dimensions [L x D x H] | 8.66" x 5.83" x 1.75" (220 x 148 x 44mm) |
| Weight | 1.477lbs (.67kg) |
| Mounting | 1 RU Rack Mounting (Hardware Included) |
| Power supply | 12v 16Watt |
| Operation temperature | 0~40C [32~104F] |