

Model Name	HTW-2
Technical	HTW-2 Wall Plate
Video Distance (HDBaseT)	<p>328ft 100m – 1080p 60Hz 24 & 36bit CAT 5e/6/6a/7</p> <p>328ft 100m – 1080p 60Hz 48bit CAT 6a/7</p> <p>328ft 100m – 4k2k 60Hz 4:4:4 CAT 6a/7</p> <p>CAT 5e/6 will achieve 328ft 100m for pixel clock <=225MHz</p> <p>CAT 5e/6 will achieve 230ft 70m for pixel clock >225MHz</p> <p>CAT 6a/7 will achieve 328ft 100m for pixel clock >225MHz</p>
Max Resolution	<p>1080p 60Hz</p> <p>1920 x 1200 @ 60Hz</p> <p>4k x 2k @ 60Hz 4:4:4</p>
Color Depth	24bit 5e/6/6a/7, 36bit 5e/6, 48bit 5e/6/6a/7
RS-232	300 - 115kbps
IR Window	30kHz-60Khz
LAN	10/100
HDMI	3D, HDCP 2.2 Compliant
Front Selections	3 Backlit Buttons (Red, Green, Blue)
LAN Connectors	Front RJ-45 with 2 LED indicators (Only yellow LED is active)
HDBaseT Connector	Rear RJ-45 WE/SS 8P8C
RS-232 Connector	4 pin 3.81mm Euro Rear
HDMI Connector	Two Type A 19 pin
VGA Connector	15 Pin High Density
Audio Connectors	3.5mm Line In/Line Out
Power Connector	2 pin 3.81mm Euro

Option Slot	Dante/AES67 Option: IPE-DTE-1 (2 Ch), IPE-DTE-2 (8 Ch) ReAX Option: IPE-ReAX-1
Mechanical	HTW-2
Housing	Aluminum front with aluminum rear enclosure
Dimensions [L x W x D]	3.728" x 2.83" (4.331" with tabs) x 1.404"
Weight	1.13g [2.5lbs]
Mounting	Wall-mounting Decora® 2 Gang
Power supply	48V DC
Power consumption	8 Watts without USB 12.9 Watts with USB
Operation temperature	0~40°C [32~104°F]
Storage temperature	-20~60°C [-4~140°F]
Relative humidity	20~90% RH [no condensation]
Package Contents	1x HTW-2 1x Paintable White Wall Plate 1x User Manual
Options	PS0094-2 48v DC 25 Watt Power Supply PS0081-1 48V PoE+ 25 Watt Power Supply IPE-DTE-1 Dante/AES67 2 Channel IPE-DTE-2 Dante/AES67 8 Channel IPE-ReAX-1 ReAX IP Control Card

Specifications subject to change without notice.