

Aurora Multimedia IPX-TC3A-CF-Pro 10G Copper/Fiber Transceiver

Compression	Zero (4K30 4:4:4/4K60 4:2:0), 1.3:1(4K60 4:4:4)
Latency	Zero Frame Latency (100us without Scaling, 3ms with Scaling)
Bandwidth	600MHz
HDCP	HDCP 2.2
HDMI	2 Inputs, 1 Output
Analog Audio	Stereo Line In/Out (3.5mm TRS Tip is Left, Ring is Right, Sleeve is Ground)
10G Ethernet (CF Version)	(1) 10G Copper RJ-45 330ft CAT 6A PoE+ & (1) 10G Fiber SFP+ (CF version)
10G Ethernet (DF Version)	(2) 10G Fiber SFP+ (DF Version)
1G Ethernet	(1) 10/100/1000M PoE+ (PSE)
RS-232	Up to 115k Baud (3.5mm TRS Tip TX, Ring RX, Sleeve Ground)
IR	Bi-Directional (3.5mm TRS Tip TX, Ring 5V, Sleeve Ground)
USB	2 x USB 2.0 Type A, 1 x USB 2.0 Micro
Expansion Cards	ExtremeUSB, Dante and ReAX Options
Webserver	Built-In Control Server
Management Software	IPBaseT Manager (free download)
3rd Party Control	Comprehensive Telnet API including Exclusive Aurora Wrapper Functions
Housing	Black Aluminum Enclosure
Dimensions [L x W x H]	175 x 102 x 27.7mm [6.875" x 4" x 1.09"]
Weight	0.453kg [1.0lbs]
Mount	Optional: Rack mount vertical, Rack mount horizontal, Under table mount
Power Supply	PoE on 1G or 10G LAN ports
Power Consumption	12.9 Watts
Operating Temperature	0 ~ 40 Celsius [32 ~ 100 Farenheit]
Storage Temperature	-20 ~ 60 Celsius [-4 ~ 140 Farenheit]
Relative Humidity	20~90% RH [no condensation]