

## Aurora Multimedia VLX-TCW2V-C-B HDMI/VGA 4K IP A/V Wall Plate Extender/Black

<b>Technical</b>	
Compression	8:1
Latency	1.5 Frames (25ms)
HDMI Inputs	2 HDMI 2.0/HDCP2.2
HDMI Outputs	1 HDMI 2.0/HDCP2.2
VGA/YPbPr Inputs	1 15 Pin HD Female
Audio Analog	Stereo Line In/Out (3.5mm TRS)
1G Copper Ethernet	RJ-45
LAN	RJ-45 10/100/1000M PoE (PSE)
Video Bandwidth	340MHz
Video support	Up to 4K2K 4:2:0 @60Hz
Audio support	Up to 32 channels & Break-away Capable
RS-232	2 qty Up to 115k Baud (3.5mm TRS)
IR	Bi-Directional (3.5mm TRS)
USB Connector	1 USB 2.0 Type A, 1 USB 2.0 Type B 2 USB 1.1 Type A
Expansion Port	Dante® Option
Interface	IR or Keypad via OSD, Webserver
<b>Mechanical</b>	
Housing	Aluminum
Dimensions [L x W x H]	2 Gang 3.728" x 2.83"(4.331" with tabs) x 1.404"
Weight	1.13g [2.5lbs]
Mounting	Wall-mounting Decora® 2 Gang
Power supply	48V DC (2 pin Euro) or 1G PoE
Power consumption	9 Watts
Operation temperature	0~40C [32~104F]
Storage temperature	-20~60C [-4~140F]
Relative humidity	20~90% RH [no condensation]