

Blackmagic Design BMD-HYPERD/ST/DAHM HyperDeck Studio HD Mini

Standards

SD Video Standards

- 525i59.94 NTSC, 625i50 PAL

HD Video Standards

- 720p50, 720p59.94, 720p60
- 1080i50, 1080i59.94, 1080i60
- 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60
- 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30

2K DCI Video Standards

- 2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI

SDI Compliance

- SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 424M, SMPTE 425M level A and B, SMPTE 2084 and SMPTE 2108-1.

SDI Metadata Support

- HD RP188 and closed captioning CEA-708. HDR Metadata supported on SDI.

Supported HDMI Formats

- 525i59.94 NTSC, 625i50 PAL,
- 720p50, 720p59.94, 720p60,
- 1080i50, 1080i59.94, 1080i60,
- 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60,
- 2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI

Audio Sampling

- Television standard 24-bit, 48 kHz sample rate.

Video Sampling

- 4:2:2 YUV

Color Precision

- 10-bit

Color Space

- REC 601, REC 709, REC 2020.

HDR Support

- Hybrid Log-Gamma, ST2084 300, ST2084 500, ST2084 800, ST2084 1000, ST2084 2000, ST2084 4000, ST2084

Multi Rate Support

- Auto detection of SD and HD.

Media

- 2 x SD card slots 1 x USB-C 3.0 expansion port for external recording of SD, HD and 2K DCI.

Media Type

- UHS-I and UHS-II SD cards.

Media Format

- Can format media to ExFAT (Windows/Mac) or HFS+ (Mac) file systems.

Supported Codecs

- ProRes HQ QuickTime, ProRes 422 QuickTime, ProRes LT QuickTime, ProRes Proxy QuickTime for all formats up to 1080p60. DNxHD 220x, DNxHD 220x MXF, DNxHD 145, DNxHD 145 MXF, DNxHD 45, DNxHD 45 MXF for 720p and 1080p HD formats up to 60fps. H.264 High 4:2:0 8-bit, H.264 Medium 4:2:0 8-bit, H.264 Low 4:2:0 8-bit for all formats up to 1080p60.

Control

Built in Control Panel

- 8 buttons for transport and device control with search dial and 2.2 inch color display.

External Control

- RS-422 deck control, SDI start/stop, timecode run. Includes Blackmagic HyperDeck Ethernet Protocol. Supports remote FTP file upload.

Software

Software Included

- Blackmagic OSBlackmagic HyperDeck SetupInternal Software UpgradeLoaded at system start, or via Blackmagic HyperDeck Setup using USB port.

Operating Systems

- Mac 10.15 Catalina,
- Mac 11.1 Big Sur or later.
- Windows 10, 64-bit.

Displays

- Built in 2.2 inch LCD for video, audio and timecode monitoring and menu settings.
- LED indicator lights above the SD media slots.

Power Requirements

Power Supply

- 1 x Internal 100 - 240V AC 50/60Hz.
- 1 x Locking 5.5mm barrel 12V DC Infor external power supply or battery use.

Power Usage

- 50 W max.

Accessories

Optional Accessories

- HyperDeck Extreme Control
- Teranex Mini Rack Shelf

Physical Installation

- One third rack unit width, 1 rack unit height.

Environmental Specifications

Operating Temperature

- 0° to 40° C (32°to 104° F)

Storage Temperature

- -20° to 60° C (-4° to 140° F)

Relative Humidity

- 0% to 90% non-condensing