

Technical	
Compression	Mimix™ 8:1
Latency	1 Frame (16.6ms)
HDMI Inputs	2 (HDMI 2.0b, HDCP 2.2)
HDMI Outputs	1 (HDMI 2.0b, HDCP 2.2)
Encryption	AES 256
Analog Audio	Stereo Line In/Out (3.5mm TRS)
1G Ethernet	RJ-45 and SFP
LAN	RJ-45 10/100/1000 PoE
Video Bandwidth	600MHz
Video Support	Up to 4K2K 4:4:4 @ 60Hz
Audio Support	Up to 12 Channels
RS-232	Up to 115k Baud (3.5mm TRS)
IR	Bi-Directional (3.5mm TRS)
USB Connector	1 USB 2.0 Type C 1 USB 1.1 Type C 1 USB 2.0 Type A 2 USB 1.1 Type A
Expansion Port	Dante® 2Ch/8Ch and ReAX™
Interface	IR or Keyboard via OSD, Web Server
Mechanical	
Housing	Black Aluminum Enclosure
Dimensions	177.04 x 150.7 x 26.42mm [6.97" x 5.93" x 1.04"]
Weight	.453kg [1lbs]
Mounting	Optional: Rack Mount Vertical, Rack Mount Horizontal, Under Table Mount
Power Supply	48v DC (2 Pin Euro) or PoE+ (LAN)
Power Consumption	8 Watts, up to 12.9 Watts with USB
Operating Temperature	0~40o C [32~104o F]
Storage Temperature	-20~60o C [-4~140o F]
Relative Humidity	20~90% RH [No Condensation]
Package Contents	1x VPX-TC1, 2x Mounting Ears