

Aten UC3022 CAMLIVE PRO (Dual HDMI to USB-C UVC Video Capture)

Connectors	
Video In	2 x HDMI Type A Female (Black)
USB Port	USB 3.2 Gen1 Type-B Male (Blue) (USB-B to USB-C and USB-B to USB-A cable package included)
Video Output	1 x HDMI Type A Female (PGM Video, Black)
Audio Inputs	1x balanced analog audio via XLR connectors 1x unbalanced audio via RCA connectors.
Video Resolution	Video input: 2160p30/25/24, 1080p60/50/30/25/24, 720p60/50 , HDMI unencrypted PGM video out: 1080p60/50/30/25/24, 720p60/50, HDMI unencrypted (Support encrypted PGM output at 2160p30/25/24, 1080p60/50/30/25/24, 720p60/50 with UVC capture disabled)
Audio Sampling	16-bit PCM audio, 44.1KHz and 48KHz
Output	Uncompressed 1080p60 & 720p60 UVC video stream with UAC audio (Uncompressed video stream is only available on USB3.1 connection)
Environmental	
Operating Temperature	0 - 40 °C
Storage Temperature	-20 - 60 °C
Humidity	0 - 80% RH, Non-Condensing
Minimum Hardware Requirements	PC/Mac: CPU: Intel® i3 Dual Core 2.8Ghz or higher RAM: 4GB or more One USB-C interface or USB-A interface Smartphone: Android device with UVC support and USB-C interface* *For detail UVC compatible device list, please refer to following info revealed by third party App. https://www.camerafi.com/supported-devices/
Connection	Bluetooth Low Energy(BLE) technology
OS Support	Windows 10 and above * Mac OS X 10.13 and above Android 5.x and above or iOS 10.1 and above , with Bluetooth 4.2 or higher supporting Bluetooth Low Energy (BLE) *Window 7 requires driver installation
Physical Properties	
Housing	Metal
Weight	0.68 kg (1.5 lb)
Dimensions (L x W x H)	13.00 x 15.18 x 4.25 cm (5.12 x 5.98 x 1.67 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.