

Panel	Panel Type:	LED-Backlit TFT LCD (TN Technology)
	Panel Size:	27.9"
	Max. Resolution:	UHD 3840 x 2160
	Pixel Pitch:	0.160 mm
	Brightness:	300 cd/m ²
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	170°/160°
	Display Colour:	1.07B
	Response Time:	3 ms
Surface Treatment:	Anti-Glare Treatment (Haze 25%),3H Hard Coating	
Frequency	Frequency (H):	30 kHz-160 kHz
	Frequency (V):	23 Hz-80 Hz
Signal Input	DisplayPort:	1.2 x 1
	HDMI:	1.4 x1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
Other Connectivity	USB:	USB HUB (2.0 x 2 / 3.0 x 1 / power outlet x 1 (5V1.5A)) / USB upstream Type-B x 1
Audio	Audio In:	Stereo Audio Jack (3.5 mm)
	Audio Out:	Stereo Audio Jack (3.5 mm)
	Internal Speakers:	3W x 2
Power	Power Supply:	Internal
	Power Requirements:	AC 100-240V, 50/60 Hz
	On Mode:	48W (On)
	Stand-by Mode:	< 0.5W
	Off Mode:	< 0.5W
Operating Conditions	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	10%-85%(non-condensing)
Storage Conditions	Temperature:	-20°C-55°C (-4°F-131°F)
	Humidity:	5%-93% (non-condensing)
Mounting	VESA FPMPI:	Yes (100 x 100 mm)
Stand	Tilt:	-5° to 23°
	Pivot:	0° to 90°
	Swivel:	±160°
	Height Adjustment:	130 mm
Security	Kensington Security Slot:	Yes

Dimensions	Product with Base (W x H x D):	659.7 x 555.4 x 224.5 mm (26.0" x 21.9" x 8.8")
	Product w/o Base (W x H x D):	659.7 x 391.0 x 49.3 mm (26.0" x 15.4" x 1.9")
	Packaging (W x H x D):	765.0 x 493.0 x 224.0 mm (30.1" x 19.4" x 8.8")
Weight	Product w/o Base:	5.3 kg (11.7 lb)
	Product with Base:	7.9 kg (17.4 lb)
	Packaging:	9.8 kg (21.6 lb)
Regulation Approval	Certifications & Compliance:	CE, CB, FCC, WEEE, RoHS, REACH, EAC
Accessories	Supplied:	Power Cord, DVI Cable, DisplayPort Cable, Warranty Card, CD
Optional Accessories	Ceiling Mount (Landscape only):	CMP-01+WMK-03
	Wall Mount (Landscape only):	WMA-01, WMK-01, WMK-03, PMK-01
	Desk mount (Landscape only):	DMC-01, ES-02