

<b>Panel</b>	Panel Type:	LED-Backlit TFT LCD (IPS Technology)
	Panel Size:	23.8"
	Max. Resolution:	FHD 1920 x 1080
	Pixel Pitch:	0.275 mm
	Brightness:	270 cd/m <sup>2</sup>
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	178°/178°
	Display Colour:	16.7M
	Response Time:	5 ms
<b>Frequency</b>	Frequency (H):	30 kHz-83 KHz
	Frequency (V):	56 Hz-75 Hz
<b>Signal Input</b>	DisplayPort:	x 1
	HDMI:	1.3 x 1
	VGA:	15-Pin D-Sub x 1
<b>Audio</b>	Audio In:	Stereo Audio Jack (3.5 mm)
	Audio Out:	Stereo Audio Jack (3.5 mm)
	Internal Speakers:	2W x 2
<b>Power</b>	Power Supply:	Internal
	Power Requirements:	AC 100-240V, 50/60 Hz
	On Mode:	18W (On)
	Stand-by Mode:	< 0.5W
	Off Mode:	< 0.5W
<b>Operating Conditions</b>	Temperature:	5°C- 35°C (41°F-95°F)
	Humidity:	20%-85%(non-condensing)
<b>Storage Conditions</b>	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-85%(non-condensing)
<b>Mounting</b>	VESA FPMPMI:	Yes (100 x 100 mm)
<b>Stand</b>	Tilt:	-5° to 20°
<b>Security</b>	Kensington Security Slot:	Yes
<b>Dimensions</b>	Product with Base (W x H x D):	555.0 x 433.0 x 226.0 mm(21.9" x 17.0" x 8.9")
	Product w/o Base (W x H x D):	555.0 x 339.0 x 46.0 mm(21.9" x 13.3" x 1.8")
	Packaging (W x H x D):	620.0 x 418.0 x 157.0 mm(24.4" x 16.5" x 6.2")
<b>Weight</b>	Product w/o Base:	3.1 kg (6.8 lb)
	Product with Base:	3.5 kg (7.7 lb)
	Packaging:	5.0 kg (11.0 lb)

<b>Regulation Approval</b>	Certifications & Compliance:	CE, LVD, FCC, BSMI, WEEE, RoHS, REACH
<b>Accessories</b>	Supplied:	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
<b>Optional Accessories</b>	Ceiling Mount (Landscape only):	CMP-01+WMK-03
	Wall Mount (Landscape only):	WMA-01, WMK-01, WMK-03, PMK-01
	Desk mount (Landscape only):	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02