

Panel	Panel Type:	LED-Backlit TFT LCD (VA Technology)
	Panel Size:	47.6"
	Max. Resolution:	FHD 1920 x 1080
	Pixel Pitch:	0.549 mm
	Brightness:	350 cd/m ²
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	178°/178°
	Display Colour:	1.07B
	Response Time:	5 ms
	Surface Treatment:	Anti-Glare Treatment (Haze 2.3%), 2H Hard Coating
Frequency	Frequency (H):	31 kHz-92 kHz
	Frequency (V):	48 Hz-85 Hz
Signal Input	HDMI:	1.3b x 1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
	Component:	RCA x 1
	Composite:	RCA x 1 (Share with Component-Y)
External Control	IR In:	3.5 mm Phone Jack
	IR Out:	3.5 mm Phone Jack
	RS232 In:	2.5 mm Phone Jack
	RS232 Out:	2.5 mm Phone Jack
	LAN:	RJ45 x 1
Other Connectivity	USB:	2.0 x 1 (Service Port / Media Playback)
Audio	Audio In:	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
	Audio Out:	Stereo Audio Jack (RCA)
	Internal Speakers:	10W x 2
Power	Power Supply:	Internal
	Power Requirements:	AC 100-240V, 50/60 Hz
	On Mode:	102W (On)
	Stand-by Mode:	< 0.5W
	Off Mode:	< 0.5W
Operating Conditions	Temperature:	5°- 40° (41°F-104°F)
	Humidity:	20%-80%(non-condensing)
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-90% (non-condensing)

Mounting	VESA FPM PMI:	Yes (400 x 400 mm & 200 x 200 mm)
Security	Kensington Security Slot:	Yes
Dimensions	Product w/o Base (W x H x D):	1081.8 x 623.4 x 59.9 mm (42.6" x 24.5" x 2.4")
	Packaging (W x H x D):	1192.0 x 773.0 x 171.0 mm (46.9" x 30.4" x 6.7")
Weight	Product w/o Base:	11.5 kg (25.4 lb)
	Packaging:	16.4 kg (36.2 lb)
Regulation Approval	Certifications & Compliance:	CCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC, FCC
Accessories	Supplied:	Power Cord, VGA Cable, RS232 Cable, Remote Control, Batteries, RS232 Daisy Chain Cable, CD
Optional Accessories	Floor Mount (Landscape only):	FMS-01, FMS-02, FMC-02
	Ceiling Mount (Landscape only):	CMP-01+LMK-01, CMP-01+LMK-02, CMP-01+WMK-03
	Wall Mount (Landscape only):	WMA-01, LMA-01, LMK-01, LMK-02, LMK-03, WMK-03
	Desk mount (Landscape only):	DTS-01
	Video Wall mount (Landscape only):	VWM-01, VWM-02
	Stand:	STD-07