

Panel	Panel Type:	LED-Backlit TFT LCD (VA Technology)
	Panel Size:	21.5"
	Max. Resolution:	FHD 1920 x 1080
	Pixel Pitch:	0.248 mm
	Brightness:	250 cd/m ²
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	178°/178°
	Display Colour:	16.7M
	Response Time:	5 ms
	Surface Treatment:	Anti-Glare Treatment (Haze 25%),3H Hard Coating
Frequency	Frequency (H):	24 kHz-83 kHz
	Frequency (V):	50 Hz-75 Hz
Signal Input	DisplayPort:	x 1
	HDMI:	1.4 x 1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
	Composite:	BNC x 2
	S-Video:	4-Pin mini DIN x 1
Signal Output	Composite:	BNC x 2
External Control	RS232 In:	2.5 mm Phone Jack
Other Connectivity	USB:	2.0 x 1 (Service Port)
Audio	Audio In:	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
	Audio Out:	Stereo Audio Jack (RCA)
	Internal Speakers:	2W x 2
	Power Supply:	External
	Power Requirements:	DC 12V, 2.5A
	On Mode:	16W (On)
	Stand-by Mode:	< 0.5W
	Off Mode:	< 0.5W
	Thickness:	3.0 mm (0.12")
	Reflection Rate:	< 1%
	Transmission Rate:	> 97%
	Hardness:	> 9H
	Operating Conditions	Temperature:
Humidity:		10%-90% (non-condensing)
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-95% (non-condensing)

Mounting	VESA FPM PMI:	Yes (100 x 100 mm & 75 x 75 mm)
Stand	Tilt:	0° to 15°
Security	Kensington Security Slot:	Yes
Dimensions	Product with Base (W x H x D):	513.2 x 368.5 x 155.0 mm (20.2" x 14.5" x 6.1")
	Product w/o Base (W x H x D):	513.2 x 324.3 x 56.2 mm (20.2" x 12.8" x 2.2")
	Packaging (W x H x D):	615.0 x 483.0 x 210.0 mm (24.2" x 19.1" x 8.3")
Weight	Product w/o Base:	6.2 kg (13.6 lb)
	Product with Base:	6.8 kg (15.0 lb)
	Packaging:	8.8 kg (19.4 lb)
Regulation Approval	Certifications & Compliance:	FCC, CCC, CB, CE, BSMI, RoHS, WEEE, REACH,
Accessories	Supplied:	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories	Ceiling Mount (Landscape only):	<u>CMP-01+WMK-03</u>
	Wall Mount (Landscape only):	<u>WMA-01</u> , <u>WMK-01</u> , <u>WMK-03</u> , <u>PMK-01</u>
	Desk mount (Landscape only):	<u>DMC-01</u> , <u>DMC-02D</u> , <u>DMS-01D</u> , <u>DMS-01Q</u> , <u>ES-02</u>