

Specifications for OneLINK Bridge Express for Vaddio HDBaseT Cameras

Dimensions & Measurements

| | |
|-----------------------|---------------------------|
| Depth | 6.5 in (16.5 cm) |
| Distance | 328 in (833.1 cm) |
| Height | 1.7 in (4.4 cm) |
| Operating Temperature | 32° to 104°F (0° to 40°C) |
| Product Weight | 3.3 lbs (1.5 kg) |
| Width | 8.4 in (21.3 cm) |

Characteristics & Features

| | |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| 3rd Party Control | <ul style="list-style-type: none">▪ RS232▪ Telnet |
| Bridged Signal | Audio and Video |
| Browser-based User Interface for Remote Control | Built-in |
| Color | Black |
| Compatible With | <ul style="list-style-type: none">▪ Cisco▪ Panasonic▪ Polycom▪ Sony▪ Vaddio |
| Extension Type | <ul style="list-style-type: none">▪ Camera▪ Camera▪ Codec |
| Input Ports | <ul style="list-style-type: none">▪ HDbT▪ Line Level Audio▪ Mic Level Audio |

| | |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| OneLINK Bridge adds | <ul style="list-style-type: none">▪ 328ft (100M) Power Video Control Extension▪ Audio Mixer▪ HDMI▪ USB 3.0 |
| OneLINK Compatibility | Native |
| Output Ports | <ul style="list-style-type: none">▪ Audio▪ HDMI▪ USB 3.0 Type B |
| Power Cord | US Cord |
| Power Supply | <ul style="list-style-type: none">▪ 1.36A▪ 48VDC |
| Power Type | Local Power |
| Quick-Connect Compatibility | No |
| Special Features | InfoComm |
| TAA Compliant | Yes |

Certifications & Warranties

| | |
|----------------|------------------------------------------------------------------------------------------------------|
| Certifications | <ul style="list-style-type: none">▪ CE▪ FCC▪ TAA▪ UL Listed |
| Warranty | 3 years |
