Wireless Connectivity

Wireless Technology	Digital DECT (1.9 GHz)
DECT Standard	6.0
Operating Range	1100' / 335.3 m
RF Bandwidth	1.72 MHz
Max Transceivers per Band	8
Wireless Modulation	Analog: GFSK
Duplex Mode	Full-Duplex (FDX)
Duplex Mode Approximate RF Sensitivity	Full-Duplex (FDX) -90 dBm

Headphone

Earpiece Design	On-Ear (Supra-Aural) / Over-Ear (Circumaural)
Earpiece Connection / Wearing Style	Headband

Number of Earpieces	Single Earpiece (Left or Right Side)
Sound Field	Mono
Controls/Microphone Location	Controls: Adjustable Boom, Earpiece (Side Unspecified) Microphone: Earpiece (Side Unspecified)
Noise Attenuation	Up to 20 dB (Active)
Frequency Response	150 Hz to 7 kHz
Total Harmonic Distortion (THD)	1%
Maximum Sound Pressure Level (SPL)	115 dB
SNR	Headphones: >71 dB

Microphone

Туре	Electret Condenser
Mic Boom Location	Interchangeable (Left or Right Side)
Pickup Pattern	Cardioid (Unidirectional)
Noise Canceling	Yes
Maximum SPL	115 dB

Wired Connectivity

Audio Connector to Source	None
Battery	
Battery Type	Headset: 1 x 26650
Battery Chemistry	Headset: Lithium-Ion
Capacity (mAh)	700 mAh
Runtime	Headset: 10 Hours
Recharge Time	2.5 Hours
Environmental	

Operating Temperature	32 to 77°F / 0 to 45°C
Storage Temperature	14 to 140°F / -10 to 60°C

Physical

Environmental Protection	None
Dimensions	7.1 x 6.3 x 3" / 18 x 16 x 7.6 cm
Weight	6 oz / 170 g (with Batteries)
Packaging Info	
Package Weight	1.135 lb

Box Dimensions (LxWxH)

8.45 x 8.4 x 3.2"