

AUDIO	
FREQUENCY RESPONSE	20-20 KHZ
ANALOG INPUT VOLTAGE	0.8 VRMS, 2.3 VP-P
ANALOG OUTPUT VOLTAGE	1.5 VRMS, 4.4 VP-P
DIGITAL	2 CHANNEL PCM
SUPPORTED SAMPLE RATES (KHZ)	32, 44.1, 48, 88.2, 96, 176, 192
LATENCY	≤60 MILLISECONDS
MUTE	AVAILABLE ON ALL OUTPUTS
AUDIO INPUTS	
AEX AUDIO	2
RCA	20
DIGITAL TOSLINK	2
DIGITAL COAXIAL	2
AUDIO OUTPUTS	
AEX AUDIO	2
RCA	22
CONTROL	
INTERFACES	RS-232, IP/LAN
ADDITIONAL CONNECTIONS	
IN-SYSTEM PROGRAMMING	USB TYPE C
12V DC TRIGGER OUTPUT	4
POWER	
TOTAL POWER CONSUMPTION	50 WATTS MAXIMUM
AC POWER	100-240 VAC
DIMENSIONS	
HEIGHT X WIDTH X DEPTH (STANDALONE UNIT)	MILLIMETERS: 88 X 440 X 234.95 INCHES: 3.5 X 17.5 X 9.25
HEIGHT X WIDTH X DEPTH (PACKAGED UNIT)	MILLIMETERS: 172 X 578 X 375 INCHES: 6.75 X 22.75 X 15
WEIGHT (STANDALONE UNIT)	8.7 LBS (3.95 KG)
WEIGHT (PACKAGED UNIT)	11.9 LBS (5.4 KG)
RACK SPACE	2U
*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. MASS AND DIMENSIONS ARE APPROXIMATE.	