

Parameter				
Input	Interface type	HDBaseT, HDMI/DVI, 3G/HD/SD-SDI, VGA, YPbPr, CVBS		
	Signal and Interface Standards	HDMI 2.0	HDMI port	HDMI 2.0, Reso up to 4K@60Hz 4: 4: 4
		HDMI1.3	HDMI port	HDMI V1.3A, Reso up to 1080P@60
		HDMI	DVI-U port	HDMI V1.3A, Reso up to 1080P@60
		DVI	DVI-U port	DVI 1.0, Reso up to 1920x1080
		VGA	DVI-U port	Reso up to 1920x1080
		YPbPr	DVI-U port	Reso up to 1080p60
		CVBS	DVI-U port	PAL, NTSC
		SDI	BNC port	Reso up to 1080p60
		VGA	VGA-DB15	Reso up to 1920x1080
		HDbaseT	RJ45 port	Reso up to 1920x1080
output	Interface type	HDbaseT, HDMI/DVI, 3G/HD/SD-SDI, VGA, YPbPr, CVBS etc		
	Signal and Connection Standards	HDMI 2.0	HDMI port	HDMI 2.0, Reso up to 4K@60, 4: 4: 4
		HDMI1.3	HDMI port	HDMI V1.3A, Reso up to 1920x1080
		HDMI	DVI-U port	HDMI V1.3A, Reso up to 1920x1080
		DVI	DVI-U port	DVI 1.0, Reso up to 1920x1080
		VGA	DVI-U port	Reso up to 1920x1080
		YPbPr	DVI-U port	Reso up to 1080p60
		CVBS	DVI-U port	PAL/NTSC
		SDI	BNC port	Reso up to 1080p60
		VGA	VGA-DB15	Reso up to 1920x1080
		HDbaseT	RJ45 port	Reso up to 1920x1080
Control	Serial control	RS-232 direct connection type	D-sub 9	Buad rate: 9600
	Network control	Fixed IP address		
	ESD Protect	±8kV (Air-gap discharge) , ±4kV (Contact discharge)		
Power	AC	AC110~240VAC, 50/60Hz		
	Power consumption	60W—160W		
Temp	Operating temp	32 - 104°F / 0 - 40°C		
	Storage Temp	-4 - 140°F / -20 - 60°C		
Humidity		20 - 90% RH (no-condensation)		
Housing		Metal		
Color		Silver gray		
Size	W*D*H	483 (mm) ×365 (mm) ×360 (mm)		