

Soundtube P350 Amplifier Class-G High Current Mono Block Amplifier

Description	P350 Class-G high current subwoofer/full range mono block amplifier
Amplifier Power	350 Watts RMS >.5% THD @ 4 Ohms, 700 Watts peak 225 Watts RMS >.5% THD @ 8 Ohms, 400 Watts peak
Crossover Frequency	Low Pass 40 - 120 Hz adjustable @ 24 dB/octave
LFE Frequency Response	20 - 500 Hz
Full Range Response	10 Hz - 20 kHz +0/- .25 dB, 5-60 kHz +0/-3 dB
Low Frequency EQ	-3 dB to +6 dB @ 30 Hz
Input Sensitivity	175 mV for full output unbalanced/ 220 mV balanced
THD	>.1% 20-20kHz below rated output power
S/N	Better than 80 dB unweighted
Damping Factor	<200
Input Impedance	22K unbalanced, 37.5K balanced
Protection Features	Soft Clipping (Subwoofer mode), Short Circuit/Overload, Thermostatic variable speed fan cooling, Thermal overload protection, Transformer thermal protection, Over current protection
Current consumption 120V	3A @ 8 ohms, 5.5A @ 4 ohms continuous
Dimensions (Overall)	17.25" W x 2.0" H x 13.25" D
Weight	17.8 lbs.