

Rockustics Pavarocci-S 8in Coax Outdoor Speaker/62Hz-20kHz/70W/Sandstone

System Type	8.0" coaxial, two-way, outdoor speaker (optional 64 Watt transformer available)
Impedance (nominal) ¹	4 Ohms (nominal)
Sensitivity dB @ 2.38 V/1 m	91.5 dB
Sensitivity dB @ 1W/1m ²	88.5 dB
Frequency Response (-3 dB) ³	87 Hz - 18 kHz
Frequency Response (-10 dB) ³	68 Hz - 22 kHz
Max. Program Power ⁴	140 W
Max. Continuous Power RMS ⁵	70 W
Max. Power SPL @ 1 m ⁶	107.0 db
Directivity Factor (Q)	3.3 (averaged 100 Hz - 10 kHz); 5.9 dB (2 kHz)
Directivity Index (DI)	4.4 (averaged 100 Hz - 10 kHz); 7.7 dB (2 kHz)
Coverage Angle (-6 dB @ 2 kHz)	75°
Coverage Angle (-6 dB @ 10 kHz)	55°
Coverage Angle (Ave from 2 to 10 kHz)	90°
Transducer- Low-Frequency Driver	203.2 mm (8.0 in.) weather resistant
Transducer- High-Frequency Driver	25 mm (1.0 in.) weather resistant
Low-Frequency Voice Coil	25 mm (1.0 in.)
Enclosure Material	Elastomer reinforced polymer with pulverised stone
Inputs	Wire lead
Color Options	Sandstone
Height	406.4 mm (16 in.)
Width	342.9 mm (13.5 in.)
Depth	317.5 mm (12.5 in.)
Weight	10.9 kg (24 lbs.)
Included Accessories	N/A
Optional Accessories	64 Watt transformer
Packaging	1 Per box