BZBGEAR BG-AVIP-HD400 HD Video Over IP System with Live Preview/Recording/Matrix and Audio De-Embedding

Encoder	
Video Input	(1) HDMI In
Video Input Connector	(1) Type-A female HDMI
HDMI Input Resolution	Up to 1080p@60Hz 444 10/12bit
Video Output	(1) HDMI Out
Video Output Connector	(1) Type-A female HDMI
HDMI Output Resolution	Up to 1080p@60Hz 444 10/12bit
Control	(1) RS232, (1) IR In, (1) IR Out, (1) LAN (PoE)
Control Connector	(1) 3-pin terminal block, (2) 3.5mm jack, (1) RJ45
Decoder	
Video Output	(1) HDMI Out
Video Output Connector	(1) Type-A female HDMI
HDMI Output Resolution	Up to 1080p@60Hz 444 10/12bit
Audio Output	(1) Audio Out (L+R)
Audio Output Connector	(1) RCA jack
Control	(1) Storage, (1) RS232, (1) IR In, (1) IR Out, (1) LAN (PoE)
Control Connector	(1) Type-A USB, (1) 3-pin terminal block, (2) 3.5mm jack, (1) RJ45
General	
Video Encoding Standard	H.264
External Power Supply	Input: AC 100~240V, 50/60Hz, Output: 12V DC 1A; PoE supported.
Power Consumption	Encoder: 4W (Max); Decoder: 3.5W (Max)
Operation Temperature	-5°C ~ +55°C
Storage Temperature	-25°C ~ +70°C
Relative Humility	10%-90%
Dimension (W*H*D)	152.0mm x 21.0mm x 100.0mm
Net Weight	Encoder: 340; Decoder: 345g