

**Bolide BK-DVR16 16-Channel 1080N Pro Hybrid Digital Video Recorder**

|                            |   |
|----------------------------|---|
| Resolution                 | VGA:1024x768,1280x720, 1280x1024, 1440x900, 1920x1080<br>HDMI:1024x768,1280x720, 1280x1024, 1440x900, 1920x1080, 2560x1440, 3840x2160   |
| Feature                    | Single/Quad/S.E.Q/  |
| <b>Record</b>              |   |
| Resolution                 | 1080N / 720P / 960H<br>IP: 1080P / 720P<br>Single IP Channel Preview Up to 2MP 30FPS Multi-Channel, Preview Only Sub-Stream   |
| Speed                      | Main Stream:<br>1080N ( 960x1080 ): 30FP<br>720P: 30FPS / Channel<br>IP: PAL: 25FPS / Channel<br>NTSC: 30FPS / Channel<br>Sub-Stream:<br>PAL704x576: 10FPS/Channel<br>NTSC704x480:10FPS/Channel |
| Video Compression          | H.265 / H.264   |
| Video System               | NTSC / PAL  |
| Operating System           | Linux (embedded)  |
| Analog video Input/ Output | 16-Channel BNC / HDMI Output  |
| IP Video Input             | Up to 4-Channels  |
| Composite Video Input      | Up to 20 Channels ( Analog & IP )   |
| Audio Input/Output         | None, Audio Over Coax Only ( Cameras Must Be Set to TVI Mode )  |
| IP-Recording Bandwidth     | 16Mbps  |
| Max. Output Bandwidth      | 80Mbps  |
| Recording Mode             | Continuous / Manual / Motion Detection / Alarm / Video Analytics  |
| Synchronous Playback       | Up to 4 Channels  |
| Network Type               | LAN, DHCP   |
| HDD Interface              | 1 SATA HDD, up to 12TB  |
| USB                        | 2x USB 2.0 ( Front )  |
| PTZ Control                | Control Over Coax, RS-485   |
| Mobile Surveillance        | Bolide Quick Connect on iOS / Android   |
| Power Supply               | DC12V / 2A  |
| Dimension                  | 9.05" x 8.46" x 1.85"   |
| Working Temperature        | 32°F~+104°F   |
| Working Humidity           | 10%~90%   |