

**Bolide SVR9504H/NDAA 4-Channel Hybrid 5MP Digital Video Recorder/NDAA Compliant**

<b>Display</b>	
Resolution	VGA:1024x768,1280x720, 1280x1024, 1440x900, 1920x1080 HDMI:1024x768,1280x720, 1280x1024, 1440x900, 1920x1080, 2560x1440, 3840x2160
Feature	Single/Quad/S.E.Q/
<b>Record</b>	
Resolution	Analog 5MP/4MP/3MP/1080P/720P/960H IP 5MP/4MP/3MP/1080P/720P/960H
Speed	Analog: 8MP: 7FPS / Channel, 5MP:12FPS / Channel, 4MP:15FPS / Channel, 1080P: PAL: 25FPS / Channel, NTSC: 30FPS / Channel IP: PAL: 25FPS / Channel, NTSC: 30FPS / Channel Sub-Stream PAL704x576: 10FPS/Channel, NTSC704x480:10FPS/Channel
Video Compression	H.265 / H.264
Video System	NTSC/PAL
Operating System	Linux (embedded)
Analog video input/output	4-Channel BNC / VGA & HDMI Output
IP Video Input	2-Channels
Composite Video Input	Up to 6 Channels ( Analog & IP )
Audio Input/Output	4 Audio In / 1 Audio Out
IP-Recording Bandwidth	12Mbps
Max. Output Bandwidth	48Mbps
Recording Mode	Continuous / Manual / Motion Detection / Alarm / Video Analytics
Synchronous Playback	4 Channels
Network Type	LAN, DHCP
HDD Interface	1 SATA HDD, up to 12TB
USB	1 USB 2.0 ( Front ), 1 USB 2.0 ( Rear )
PTZ Control	Control Over Coax, RS-485
Mobile Surveillance	Bolide Quick Connect on iOS / Android
Power Supply	DC12V / 2A
Dimension	11.8" x 8.2" x 1.89"
Working Temperature	32°F~+104°F
Working Humidity	10%~90%