

PreSonus HP4 4-Channel Headphone Amplifier (1/3U)

Inputs	
Connector Type	¼" TRS, balanced
THD+N	0.0025%, 1 kHz, unity gain
Max Input Level	+18 dBu, <0.5% THD+N, unity gain
Input Impedance	10 kΩ
Frequency Response	20 Hz - 20 kHz, ±0.5dB
Monitor Outputs	
Connector Type	¼" TRS, asymmetrical, impedance-balanced
THD+N	0.0025%, 1 kHz, unity gain
Max Output Level	+18 dBu, <0.5% THD+N
Output Impedance	51Ω
Frequency Response	20 Hz - 20 kHz, ±0.5dB
Headphone Outputs	
Connector Type	¼" TRS, stereo
Max Output Power	130 mW/Ch., <0.5% THD+N, 60Ω load
Frequency Response	20 Hz - 20 kHz, ±0.5 dB, 60Ω load
Headphone Impedance Working Range	32Ω - 600Ω
Power	
External Adapter Type	+12 VDC, 1000 mA, center pin positive
Physical	
Dimensions	1/3U rack-mount (with standard rack tray, not included)
Height	1.75" (44.45 mm)
Depth	5.5" (139.7 mm)
Width	5.5" (139.7 mm)
Weight	5 lbs (2.27 kg)