

## Appotronics GU25KA HDBaseT Laser Projector WUXGA 1920x1200 / 25000 ANSI lm / 100000:1 / Lens Shift / Edge Blending

Full HD 1080P compatible	1080P compatible
Lens shift Funktion	Motorized optical axis shift
User logo	Yes
Kensington Slot	Yes
Warping	Yes
Edge Blending	Yes
Password protection	Yes
Lan network compatible.	Yes
Refresh rate	WUXGA 120 Hz / 4K 60 Hz
Display Technology	DLPx3 / DLP Projection System
Resolution	1920 x 1200
Brightness Output	26000 lm center / 25000 lm ANSI
Light Source Type	Red and Blue Laser + ALPD Laser
Life Source Lifetime	20000 h
Contrast	100000:1
Uniformity	95%
Display Gamut	REC.709
Edge Blending	Horitonal & Vertical EdgeBlending
Optional Lenses	0.7:1, 0.8:1, 0.89-1.29:1, 1.28-1.81:1, 1.6-2.29:1, 2.13-4.16:1, 3.66-5.94:1, 4.5-8.2:1
Screen Size	70" ~ 1000"
Keystone	Vertical & horizontal $\pm 20^\circ$
Band Width	600 MHz
Optical Axis Shift	Vertical $\pm 90\%$ / Horizontal $\pm 40\%$ / Powered
I/O	HDMI x1 / DVI-D x1 / HDBaseT x1 / VGA x1 / DisplayPort x1 / SDI x2 / RS-232 IN&OUT x2 / Remote IN&OUT x2 / USB x1 / RJ-45 x1 / 3D SYNC IN&OUT x2 / IR 3D out x1
Power Supply	100-240V AC 50/60Hz
Power Consumption	Standard 2500 W / Standby <0.5 W
Structure Measurements	32" x 24" x 11"
Structure Weight	150 lbs
Noise	49 dB
Working Environment	

Temperature	32°F ~ 113°F
Working Environment Humidity	20% ~ 80% (no condensation)