

**Appotronics SK15KAS 4K/WUXGA RGBX Full Spectrum Laser Projector / 15,000lm / >=110% Rec.709 / IP6X**

MODEL	SK15KAS SK13KAS SK11KAS SU15KAS SU13KAS SU11KAS
Display Technology	DLP*1, DLP Projection System
Panel Size	0.8"DMD
Resolution	3840×2400 1920×1200
Brightness	1
Output	15000lm/16000lm (Center), 13000lm/14000lm (Center), 11000lm/12000lm (Center), 15000lm/16000lm (Center), 13000lm/14000lm (Center), 11000lm/12000lm (Center)
Light Source Type	ALPD5.0 Full Color Laser Light Source
Light Source 6 Lifetime	20000h
Contrast 2	>=100,000:1
Uniformity	>=92%
Display Gamut7	>=110% Rec.709
Edge Blending	Horizontal & vertical edge blending
Optional Lenses	0.7~0.85:1; 0.85~1.1:1; 1.14~1.51:1; 1.5~2.4:1; 2.4~3.8:1
Screen Size	70"~800"
Geometric Correction	Corner keystone, trapezoidal, curved surface, multi-point up to 33x33 points
Optical Axis Shift	Vertical +/-100% Horizontal +/-40% Powered
Signal Interfaces	HDMI2.0*2 (4K/60P), DVI-D*1, DP1.2 (4K/60P), HDBaseT 1.0*1 (Optional9), 3D SYNC in*1, 3D SYNC out*1, IR 3D out*1
Dynamic Contrast Syn Signal Interfaces	MULT SYNC in*1, MULT SYNC out*1
Control Interfaces	Ethernet RJ45, RS232, Remote IR in/out, USB-B
Other Interfaces	USB-A
12V External Power Supply Port	Power 12V 1A
Power Supply	100~240VAC 50/60Hz
Power Consumption Standard	<=1050W <=800W <=700W <=1050W <=800W <=700W
Standby	<=0.5W (ECO Mode)
Orientation	360° Installation
Noise 8	<=40dB <=38dB <=37dB <=40dB <=38dB <=37dB
Structure Measurements3	21.16 × 20.08 × 7.48 inches
Weight 4	62.83 lbs

