

Appotronics SU11KAS RGBX Laser 4K/WUXGA Projector 11000lm 100000:1 Contrast IP6X

Display Technology	DLP*1, DLP Projection System
Panel Size	0.8"DMD
Resolution	3840×2400 1920×1200
Brightness	15000lm/16000lm (Center) 13000lm/14000lm (Center) 11000lm/12000lm (Center) 15000lm/16000lm (Center) 13000lm/14000lm (Center) 11000lm/12000lm (Center)
Light Source Type	ALPD5.0 Full Color Laser Light Source
Light Source Lifetime	20000h
Contrast	≥100,000:1
Uniformity	≥92%
Display Gamut	≥110% Rec.709
Edge Blending	Horizontal & vertical edge blending
Optional Lenses	0.7~0.85:1;0.85~1.1:1;1.14~1.51:1;1.5~2.4:1;2.4~3.8:1
Screen Size	70"~800"
Geometric Correction	Corner keystone, trapezoidal, curved surface, multi-point (up to 33x33 points)
Optical Axis Shift	Vertical ±100% Horizontal ±40% Powered
Signal Interfaces	HDMI2.0*2(4K/60P) DVI-D*1 DP1.2(4K/60P) HDBaseT1.0*1(Optional9) 3D SYNC in*1 3D SYNC out*1 IR 3D out*1
Dynamic Contrast Syn Signal Interfaces	MULT SYNC in*1 MULT SYNC out *1
Control Interfaces	Ethernet Port RJ45; Serial Port RS232; Remote IR in/out; USB-B
Other Interfaces	USB-A 12V 1A
Power Supply	100~240VAC 50/60Hz
Power Consumption	Standard ≤1050W ≤800W ≤700W ≤1050W ≤800W ≤700W Standby ≤0.5W(ECO Mode)
Orientation	360° Installation
Noise	≤40dB ≤38dB ≤37dB ≤40dB ≤38dB ≤37dB
Structure Measurements	21.16 × 20.08 × 7.48 inches
Weight	62.83 lbs
Working Environment Temperature	32°C~104°C
Storage Temperature	14°C~140°C
Humidity	20%-80%(No Condensation)